



TOUCH DYNAMIC

IMPROVING TOUCH TECHNOLOGY

CS200

888.508.6824



WWW.TOUCHDYNAMIC.COM

The CS200 is Touch Dynamic's newest state of the art All-in-One System. The CS200 delivers the power required to run your applications and will give you the upgradability you demand. The CS200 features 4 Powered Serial Ports, 4 USB v2.0, 1 LPT, LAN (10/100) and much more. The CS200 has the sharp look you desire and the reliability you need.

HIGHLIGHTS

- 4 serial ports, powered
- 4 USB 2.0 ports in rear (2 powered)
- Speed and Reliability in a POS Terminal
- Serviceable Design

FEATURES

- 180W Power Supply
- 15" Bright LCD w/0°-70° viewing angle
- 10/100 Intel LAN
- Intel Chipset

OPTIONS

- Integrated Credit Card Reader
- Integrated Digital Persona UareU
- Integrated Wireless 802.11b/g
- Integrated 12" Rear LCD
- Integrated Pole Display
- Integrated CDROM,CDRW / DVD,DVDRW

TOUCH DYNAMIC
17 Camptown Rd.
Irvington, NJ 07111

888-508-6824
www.touchdynamic.com

Mainboard	
Motherboard	B82
CPU Support	Celeron 2.0Ghz, Pentium IV 2.4Ghz, Pentium IV 2.8Ghz
Chipset	Intel 852GME (GMCH Memory Control Hub) and ICH4
System Memory	Supports 2xDDR DIMM 266/333 256MB RAM up to 2GB RAM
Graphic Memory	UMA Shared memory up to 64MB
LCD / Touch Panel	
LCD Size	15" TFT
Brightness (cd/m ²)	250-350
Maximum Resolution	1024x768
Touch Screen Type	ELO Resistive
Tilt Angle (Degree)	0-70
Storage	
HDD	3.5" 80GB HDD-Segate
ODD	1xSlim CD-ROM, CDRW / DVD or DVDRW
Flash Memory	Compact Flash (Type I & II)
Expansion	
Mini-PC Socket	1
External I/O Ports	
I/O Ports	
PS/2 Keyboard & PS/2 mouse	1 shared port with splitter
PS/2 Mouse	1
USB	2 front USB 2.0, 2 rear USB 2.0 (Powered)
Serial/COM	4xPowered COM ports (pin1 / pin 9 support +5V / +12V by jumper)
Parallel	1
LAN (10/100)	1 (RJ45)
2nd VGA	1 male type connector with power
Cash Drawer Port	1 (12V / 24V)
Internal Speaker	2x2Watt
Audio	Optional Line out, mic in
Control Indicator	
Power Indicator	1
Indicator LED	2 (power, HDD)
Power	
Power Supply	Internal 180W ATX switching mode power supply
Environment	
EMC & Safety	FCC Class A, CEMark, LVD
Operating Temperature	5°C ~ 35°C (41°F ~ 95°F)
Storage Temperature	-20°C to 60°C
Operating Humidity	20% - 80% RH non condensing
Storage Humidity	20% - 85% RH non condensing
Peripheral	
Input Device (optional)	
Magnetic Card Reader	3 Tracks (RS-232 / PS2 Interface)
Biometric	Integrated Digital Persona UareU
Output Device	
Second Display	12.1" TFT LCD
Customer Display	VFD / LCD
Dimension (WxDxH)	14.9 x 14.3 x 14.1 in
Weight	N.W. 20lbs / G.W. 28lbs
OS Support	Windows XP, WePOS, XP Embedded, XP Professional for Embedded, WIN 2000 Pro Embedded
	Win NT 4.0, Linux, Redhat 7.2