

HIGHLIGHTS

- Bounce Free Desktop Design
- Optional Integrated MSR or Pole Display
- Wall Mountable
- Spill Proof
- Internal Speakers
- Viewing Angle 0° - 90°



SPECIFICATIONS

LCD Panel Size	15" TFT Active Matrix Display
Touch Panel	Fujitsu 4 -wire (optional ELO 5-wire Resistor w/controller (RS232))
Maximum Visual Size:	304(H) x 228(V) mm
Pixel Pitch	0.297(H) x 0.297(V) mm
Maximum Resolution	1024 x 768 pixel
Contrast Ratio	400:1 (typical)
Brightness	250 cd/m ²
Response Time	25ms (typical)
Display Color	16.7M (max)
PC Interface	Standard PC RGB Analog Interface
Signal Input Connector	DB Type 15PIN connector
On Screen Controls	Yes
Integrated Speakers	Yes
Signal Sync.	TTL positive or negative
Refresh Rate	H-Sync: 30 - 60 KHz, V-Sync: 50 - 75Hz
Power Supply	DC 12V 4.16A DC Power Adapter
Power Consumption	36W (MAX)
USB Function	1* USB ver 2.0 Connector
Case Color	Black
Product Size	8.5 x 10 x 13.5 in
Weight	12 lbs
Fixed Type	Desk Mount & Wall Mount (VESA Standard)
OPTIONS	
MSR Card Reader	ISO Track 1/2/3 MSR (keyboard wedge interface)
Smart Card Reader	Yes
Customer Display	2 x 20 VFD Pole Display with serial port interface

WWW.VERMONTSYSTEMS.COM

Vermont Systems, Inc.
12 Market Place
Essex Jct, VT 05452
877.883.8757